



## Color Matching

- Available in most formulations.
- Capable of producing custom colors and color matches, utilizing state-of-the-art technology.
- Computerized laboratory equipment facilitates batch to batch reproducibility.
- Bi colors available up to .750", without laminating.

## Laminations

- Permanent laminations double the available thickness ranges of our product line.
- Specialty and customer supplied material can be incorporated to add value and make use of our advanced adhesive technology.
- Capable of laminating films, foils and non woven.
- Available up to 2" thick as bi-lamination using Polyvinyl Chloride foam (PVC).

## Fire Retardant (F Series)

- Available on a quotation basis only.
- Self-extinguishing formulation conforms to UL 94 requirements.
- Gray is the standard recognized component. (Other colors available upon request).
- Available in a range of densities of 6 to 35 pounds per cubic foot.

## Reeling/Spooling

- Available in V700 Series and Up
- Width availability from .188" to 1.625".
- The standard core is 8".  
12" core available upon request.
- Jumbo reels available in multiples of 4 reels from .500" to 1.00" only.
- Length availability is based on thickness of the material.

## Die Cutting

- Parts 10" in length (or less) and 18" in width (or less) and .500" in thickness (or less) are usually +/- .049" in dimensions. Special tighter tolerance dies may be available for thin materials (under .031" in thickness).
- Parts greater than 10" in length or 18" in width are +/- .125" in dimensions (note: maximum length is 17"; maximum width is 28"; maximum thickness is 1").

General Note: All dies are verified for tolerances prior to final acceptance by Gaska Tape Inc. Certain special configurations may require increased tolerances. Customers will be contacted for mutual agreement of new tolerances prior to production of parts.

## Chopped Pieces (Cut to Length)

- Parts of 45" in length (or less) and 13" in width (or less) are +/- .250" in dimensions
- (Note: Maximum length is 45"; maximum width is 13"; maximum thickness is .750").

General Note: As the part becomes thicker (especially above .500" thick), the part becomes beveled on the leading trailing edges.



**Color Matching**



**Laminations**