



Description

Gaska Tape's VK Series products are available as a medium or high density closed-cell Polyvinyl Chloride foam. Designed specifically as a "spacer in structural silicone curtain wall applications."

Both products are coated on each side with an aggressive, high performance S3 solvent acrylic pressure-sensitive adhesive and covered with a 5 mil blue polypropylene film liner.

Can also be used in a wide variety of other applications that previously relied on costly high-density urethane gaskets for spacing, vibration dampening or cushioning.

Performance Characteristics

- Resilient weather seal.
- Compatible with most chemical cured silicone sealants.
- VK Series spacer materials have a six-month shelf life on Solvent Adhesives.
- VK Series offers a good balance of peel strength (PSTC-1) at 2-lbs./linear inch and shear strength (PSTC-7) at 30 hours.
- VK Series is a cost effective substitute for Polyurethane foam substrates.
- VK Series also offers good adhesion to stainless steel, glass, aluminum, painted metal and vinyl. It is a cost-effective and viable gasket option for a variety of other industries including industrial equipment manufacturing, automotive glass/windshield and building construction.
- Black color standard.
- Other colors available upon request.

• Several well known silicone manufacturers have approved the VK Series in compatibility testing with their silicones. Results available upon request.

• VK Series is a very economical alternative to costly high-density urethanes.

• Good chemical resistance and is compatible with silicone materials, has a workable service temperature range, plus good weatherability.

• Inherently resistant to fire, ultraviolet rays, most chemicals, acids and solvents.

Industry Applications

- Automotive
- Construction
- H.V.A.C.
- Industrial
- Leisure
- Transportation
- Retail

VK Series

Spacer Tape

Roll Sizes

Available Thicknesses:

VK1826SA .031" - .375" (0.8mm - 9.5mm)

VK2526SA .031" - .250" (3.2mm - 6.4mm)

Available Widths:

.250" - 57" (6.4mm - 1448mm)

Available Lengths:

25' - 302' (7.7M - 92M)

Benefits & Features

Characteristics common to all Gaska Tape closed-cell vinyl foam products include the ability to make a long life seal against air, moisture, light and dust penetration. They cushion and absorb vibration and shock. They also insulate in thermal, electrical and sound applications.

Typical Physical Properties*

Test Method		VK1826SA	VK2526SA
ASTM D-1056	Density (lbs./cu.ft. ³) (kg/m ³)	19	25
		304	400
ASTM D-2240	Hardness (shore 00)	65	90
ASTM D-1056	Compression Deflection @ 10% (psi) kPa	15	25
		103	172
ASTM D-1056	Compression Set @ 10%	2.5%	2.3%
ASTM D-1056	Water Absorption (% by volume)	2.2%	1.2%
ASTM D-412	Tensile Strength (psi) kPa	85	175
		586	1207
ASTM D-412	Percent Elongation	70	90
ASTM C-518	Thermal Conductivity (k factor) (btu-in./hr.·sq.ft. °F) W/mK	0.29	0.33
		0.044	0.048
Recommended Service Temperature (°F) (°C)		-10 - 210 -23 - 100	-10 - 210 -23 - 100
Recommended Application Temperature (°F) (°C)		50 - 110 10 - 45	50 - 110 10 - 45
Fungi Resistance		Good	Good
Oxidation Resistance		Good	Good
Weather Resistance		Good	Good

Notes:

Gaska Tape VK Series Spacer has a six-month shelf life on Solvent Adhesives.

(1) Gaska Tape Procedure

Typical performance properties and characteristics are based on samples tested and are not guaranteed for all samples of this product.

Data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided. This data is not to be used for specification purposes.

Warranty

Gaska Tape Inc.® warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of invoice, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc.® will be pleased to provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc.® makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.

International Inquiries:
Phone: 00-574-294-5431

1810 W. Lusher
P.O. Box 1968
Elkhart, IN 46515-1968

 **Gaska Tape Inc.**
INNOVATORS IN FOAM AND TAPES
www.gaska.com

Phone: 574-294-5431
Fax: 574-293-4504
Toll free: 800-423-1571
email: sales@gaska.com

