



DESCRIPTION

Gaska Tape's C800 Series line of Cling Foam[®] offers a choice of materials depending upon the requirements of the application. The C800 Series is low density closed cell Polyvinyl Chloride foam with the unique ability to bond to non-porous surfaces without an adhesive. It comes on a special "high gloss" paper to protect the cling surface. Cling Foam[®] leaves no residue when removed.

C810 is the same low density product; coated on the opposite laminating side with a pressure sensitive adhesive.

ROLL SIZES

Available Thicknesses:
.063" (1.6mm)

Available Widths:
.250" - 57" (6.4mm – 1448mm)

Available Lengths:
150' - 302' (46m- 92m)

PERFORMANCE CHARACTERISTICS

- Prevents abrasion and movement of separated material.
- C800 can be laminated to VK Series, Polyethylene, or Cork.
- Available for die cutting when laminated.
- Bonds aggressively without adhesive.
- Used extensively for glass separator pads.
- Economical and disposable after use.
- Natural color standard, other colors available upon request.

Test Method- Typical Physical Properties	C800
ASTM D-1667 Density	8 lbs/ft³ 128 kg/m³
ASTM D-2240 Hardness (shore 00)	27
ASTM D-1667 Compression Deflection @ 25%	3.75 psi 25.8 kPa
ASTM D-412 Tensile Strength	59 psi 407 kPa
ASTM D-412 Percent Elongation	145
Recommended Service Temperature	-40 - 180 °F -40 - 82 °C
Recommended Application Temperature	50 - 110 °F 10 - 40 °C

Data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided. This data is not to be used for specification purposes.

Additional Information:

You will find the following pages on our website helpful as you consider our products and configurations.

- [Product Description](#)
- [Die Cutting Descriptions](#)
- [Standard Lead Times](#)
- [Standard Product List](#)
- [Manufacturing Tolerances](#)
- [Vinyl Foam Typical Properties](#)

Market & Application info. is also available on our Website.

Please email us for more information:
salesorders@gaska.com

WARRANTY

Gaska Tape Inc.[®] warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of invoice, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc.[®] will provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc.[®] makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.