

DESCRIPTION

GHB[®], Gaska Hi Bond, tapes are high-performance acrylic fastening systems. They can be used in a variety of applications where permanent fastening is accomplished without the aid of screws or rivets. GHB[®] tapes are available in a variety of systems to aid in your particular need whether it's fastening to glass, steel, aluminum or plastics.

4026WH Series

Tape Thickness (without liner)	Description	Temperature Resistance	Solvent Resistance	Relative Adhesion	Application Ideas	Liner Type
White .025, .045, .080"	White foamed adhesive bonds to a variety of steel, aluminum, and other high-energy substrates.	200°F	Excellent	LSE Good HSE Excellent	Utility trailers, buses, ambulances and specialty vehicles requiring a clean looking side sheet overlap.	4 mil Green PE Liner

4526BK Series


Tape Thickness (without liner)	Description	Temperature Resistance	Solvent Resistance	Relative Adhesion	Application Ideas	Liner Type
Black .025, .045, .063"	Gray core, Black adhesive best suited for powder coated metals, ABS plastics, and some painted metal applications.	180°F	Excellent	LSE Excellent HSE Good	Works well on clear polycarbonate substrates where a black adhesive is desirable, Muntin Bars	5 mil Red PE Liner

4726GY Series

Tape Thickness (without liner)	Description	Temperature Resistance	Solvent Resistance	Relative Adhesion	Application Ideas	Liner Type
Gray .045, .090"	Gray core best suited for powder coated metals, ABS plastics, and some painted metal applications.	200°F	Excellent	LSE Good HSE Excellent	Marine Industry, Utility Trailers, and aids in vibration dampening.	5 mil Red PE Liner

6626CL Series

Tape Thickness (without liner)	Description	Temperature Resistance	Solvent Resistance	Relative Adhesion	Application Ideas	Liner Type
Clear .020, .030, .040" .060, .100"	Clear acrylic with good adhesion for joining objects that are transparent, such as glass and polycarbonate substrates.	200°F	Excellent	LSE Fair HSE Good	Mounting objects to mirrors, sealing skylights, and lamination glass panels.	.020, .030, .040" thicknesses 5 mil Red PE Liner .060, .100, .120" thicknesses 7 mil White PE Liner (with minimums)



Roll Sizes

Product #	Thickness	Cast Width	Length	Foam/Liner Colors
4026WH Series				
GHB4026WH	.025"	17"	216'	White/Green Liner
GHB4026WH	.045"	36"	108'	White/Green Liner
GHB4026WH	.080"	17"	54'	White/Green Liner
4526BK Series				
GHB4526BK	.025"	17"	216'	Black/Red Liner
GHB4526BK	.045"	36"	108'	Black/Red Liner
GHB4526BK	.063"	17"	108'	Black/Red Liner
4726GY Series				
GHB4726GY	.045"	36"	108'	Gray/Red Liner
GHB4726GY	.090"	17"	108'	Gray/Red Liner
6626CL Series				
GHB6626CL	.020"	17"	216'	Clear/Red Liner
GHB6626CL	.030"	17"	216'	Clear/Red Liner
GHB6626CL	.040"	36"	108'	Clear/Red Liner
GHB6626CL	.060"	17"	108'	Clear/White Liner
GHB6626CL	.100"	17"	108'	Clear/White Liner

WARRANTY

Gaska Tape Inc.® warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of invoice, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc.® will be pleased to provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc.® makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.

1810 W. Lusher Ave.
P.O. Box 1968
Elkhart, IN 46515-1968

Manufactured in USA
www.gaska.com
Email: salesorders@gaska.com

Phone: 574-294-5431
Toll Free: 800-423-1571
Fax: 574-389-9701
574-293-4504

International Inquiries:
Phone: 00-574-294-5431

Rev 11/2022