



DESCRIPTION

Gaska Tape's EG Series are high performance closed-cell, cross linked polyolefin foam tapes, coated on both sides with a highly aggressive acrylic pressure sensitive adhesive, that adheres well to a wide variety of surfaces. These products are available with a blue polyolefin film liner or an 84# polycoated two side, brown kraft liner.

This product has been tested according to AAMA specifications. It exceeds specification requirements for Expanded Cellular Glazing Tape, Type 1.

ROLL SIZES

Available Thicknesses:

- EG 626 / 620** .031" (.8mm)
- EG 426 / 420** .063" (1.6mm)
- EG 426BK / 420BK** .125" (3.2mm)

Available Widths:

.250" - 57" (6.4mm – 1448mm)

Available Lengths:

50' - 400' (15m- 122m)

AAMA Test Method- Typical Physical Properties		EG
2.9.3	Low Temperature	No Cracking
2.14	Compression Deflection	
	Test A	7 psi
	Test B	6 psi
2.15	Compression Set	1%
2.16	Water Absorption	3%
2.17	Water Penetration	2%
2.18	Tensile Adhesion	
	@ 77°F	330% @ 75 psi
	@ 120°F	280% @ 50 psi
	@ 32°F	310% @ 90 psi
2.19	Peel Adhesion	
	@ 120°F	7 lbs/linear in.

Data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided. This data is not to be used for specification purposes.

WARRANTY

Gaska Tape Inc.® warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of invoice, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc.® will provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc.® makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.

PERFORMANCE CHARACTERISTICS

- Polyolefin foam tapes provide excellent sealing, durability and are conformable to irregular surfaces.
- Closed cell structure provides sealing, cushioning, thermal insulation, deadens sounds, and eliminates excessive vibration.
- Aggressive adhesive provides excellent initial tack to a wide variety of surfaces commonly used in the window assembly industry.
- EG products perform well over a broad temperature range and are excellent in all types of glazing applications.
- Available in black or white.

Additional Information:

You will find the following pages on our website helpful as you consider our products and configurations.

- [Product Description](#)
- [Die Cutting Descriptions](#)
- [Standard Lead Times](#)
- [Standard Product List](#)
- [Manufacturing Tolerances](#)
- [Vinyl Foam Typical Properties](#)

Market & Application info. is also available on our Website.

Please email us for more information:
salesorders@gaska.com