



DESCRIPTION

Gaska Tape's EM Series is a cost effective closed-cell, cross linked polyolefin foam tape. It is coated on both sides with a high strength adhesive that adheres well to a wide variety of surfaces for medium or light duty mounting.

PERFORMANCE CHARACTERISTICS

- Polyolefin foam tapes provide excellent sealing, durability and are conformable to irregular surfaces.
- Closed cell structure provides sealing, cushioning, thermal insulation, deadens sounds, and eliminates excessive vibration.
- Aggressive adhesive provides excellent initial tack to a wide variety of surfaces commonly used in the mounting industry.
- EM products perform well over a broad temperature range and are excellent in all types of mounting applications.
- Available in black or white.

ROLL SIZES

Available Thicknesses:

EM426 .063" (1.6mm)

EM626 .031" - (0.8mm)

Available Widths:

.250" - 57" (6.4mm – 1448mm)

Available Lengths:

50' - 400' (15m- 122m)

Test Method- Typical Physical Properties	EM426	EM626
Density	4 lbs/ft ³	6 lbs/ft ³
QA3012 ⁽¹⁾ Tensile Adhesion (T Block)	70 psi	100 psi
QA3002 ⁽¹⁾ Peel Adhesion	4 pli	4 pli
QA3006 ⁽¹⁾ Holding Power	1 psi	1 psi
QA3030 ⁽¹⁾ Lap Joint (Dynamic) Shear	60 psi	90 psi
Recommended Service Temperature	-40 - 160 °F -40 - 70 °C	-40 - 160 °F -40 - 70 °C
Recommended Application Temperature	50 - 110 °F 10 - 45 °C	50 - 110 °F 10 - 45 °C

(1) Gaska Tape Procedure

Data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided. This data is not to be used for specification purposes.

Additional Information:

You will find the following pages on our website helpful as you consider our products and configurations.

- Product Description
- Die Cutting Descriptions
- Standard Lead Times
- Standard Product List
- Manufacturing Tolerances
- Vinyl Foam Typical Properties

Market & Application info. is also available on our Website.

Please email us for more information:
salesorders@gaska.com

WARRANTY

Gaska Tape Inc.® warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of invoice, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc.® will provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc.® makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.