



Underwriters Laboratories Recognized Components File # E58620 – Dec. 2022 Update

There are two product lines: The F series of PVC foams and the PSF series of Eco Seal® Polyester foams. Recognized color in file is gray.

F Series: Polyvinyl chloride flexible foam, furnished in rolls.

Designated as: FR06PV to FR15PV (where the two numbers represent the average density in lbs./ft³)

- Applies to F series of Density Range 5.9 to 15.0 lbs./ft³
(e.g. F600GY, F800GY, F1100GY, F1500GY, etc.)
 - Thicknesses from 0.060" to 0.490" rated UL94 HF-1
 - Thicknesses above 0.490" rated UL94 HBF

PSF version of Eco Seal® Series: Polyester flexible foam, furnished in rolls.

Designated as: PSF04 to PSF15 (where the two numbers represent the average density in lbs./ft³)

- Applies to PSF version of Eco Seal® Series of Density Range from 4.5 to 15.5 lbs./ft³
(e.g. PSF600GY, PSF1000GY, PSF1500GY, etc.)
 - Thicknesses from 0.032" to 0.250" rated UL94 HF-1
 - Thicknesses of 0.260" and above rated UL94 HBF

Designated as: PSF16 to PSF31 (where the two numbers represent the average density in lbs./ft³)

- Applies to PSF version of Eco Seal® Series of Density Range from 15.6 to 31.0 lbs./ft³
(e.g. PSF1600GY, PSF2100GY, PSF3000GY, etc.)
 - Thicknesses from 0.020" to 0.394" rated UL94 HB

CDH Updated 12/22/22