



DESCRIPTION

Gaska Tape's V1520 Series product is a medium density closed-cell Polyvinyl Chloride foam coated both sides with an aggressive, pressure sensitive adhesive.

Logs coated with adhesive on both sides are slit in half and rewrapped at no additional charge to eliminate possible gapping during transit.

This product has been tested and approved according to AAMA specifications for Expanded Cellular Glazing Tape.

ROLL SIZES

Available Thicknesses:

V1520 .063" - .500" (1.6mm – 12.7mm)

V1526 .063" - .500" (1.6mm – 12.7mm)

V1526SA .063" - .500" (1.6mm – 12.7mm)

Available Widths:

.250" - 57" (6.4mm – 1448mm)

Available Lengths:

25' - 302' (7.6m- 92m)

PERFORMANCE CHARACTERISTICS

- Absorbs shocks, cushions, deadens, sound and eliminates excess vibration.
- Excellent in glazing applications.
- **V1520** is provided on an 84# polycoated two sided brown kraft liner.
- **V1526** is the same medium density foam; A3 adhesive coated on both sides, but incorporating a 4 mil blue polypropylene film liner.
- **V1526SA** is coated both sides with a solvent acrylic pressure sensitive adhesive, S3, and a 4 mil blue polypropylene film liner. Gaska Tape's V1526SA has a six-month shelf life from date of invoice.
- Effectively functions as a thermal break and insulator.
- Black color standard, other colors available upon request.
- Sulfur-Free

Test Method-Typical Physical Properties	V1520
ASTM D-1667 Density	15 lbs/ft³ 240 kg/m³
ASTM D-2240 Hardness (shore 00)	40
ASTM D-1667 Compression Deflection @ 25%	7 psi 48 kPa
ASTM D-1667 Compression Set @ 25%	8 %
GTP ⁽¹⁾ Water Absorption (% by volume)	1.0 %
ASTM D-412 Tensile Strength	80 psi 550 kPa
ASTM D-412 Percent Elongation	160
ASTM C-518 Thermal Conductivity (K Factor)	0.30 btu-in./hr-ft²-°F 0.043 W/mK
Recommended Service Temperature	-30 - 200 °F -35 - 90 °C
Recommended Application Temperature	50 - 110 °F 10 - 45 °C

(1) Gaska Tape Procedure

Data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided. This data is not to be used for specification purposes.

WARRANTY

Gaska Tape Inc.® warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of invoice, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc.® will provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc.® makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.

Additional Information:

You will find the following pages on our website helpful as you consider our products and configurations.

- [Product Description](#)
- [Die Cutting Descriptions](#)
- [Standard Lead Times](#)
- [Standard Product List](#)
- [Manufacturing Tolerances](#)
- [Vinyl Foam Typical Properties](#)

Market & Application info. is also available on our Website.

Please email us for more information:
salesorders@gaska.com